

TOP 20 ASA PRODUCT					
No.	Product Name	Characteristic	Industry / Application	Mixing Ratio	Pot Life
1	Asamould 213 A	Good heat resistant, hardness and	Vacuum forming mould, jigs & fixtures.	2	20 mins.
	Asamould 213 B	dimensional stability, machinable, sandable		1	
	Asamould 213 C	and polishable.		3	
2	Asacoat MT 1289 A	Grey colour, medium viscosity, solvent-free.	Coating for polystyrene foam, suitable for	10	20 mins.
	Asacoat MT 1289 B	Coating & touch-up purpose.	sculptor, artist and event decoration.	3	
3	Asasin 2829	Low viscosity, transparent and gloss surface	Souvenirs industry; laminating on metal plate,	2	30 mins.
	Asahard 3515	finishing. Laminating & flooring purpose.	badges, name tages and etc.	1	
4	Asapu 4065/2 A	Structural foam, 3 to 4 times expansion, light	Wood imitation parts for furniture, automative,	1	1 min.
	Asapu 4065/2 B	weight and hard.	building industries.	1.1	
5	Asapu 115 A	Polyurethane foam, 10 times expansion, good	As insulator in fridge, coolbox, or adhesive of	1	45 seconds
	Asapu 115 B	heat and sound insulation, light weight.	polystyrene foam.	1	
6	Gelcast 355 A	Milky color, high viscosity, fast curing. Non	Paper pulp industry, 1st layer of paper pulp	5	30 mins.
	Gelcast 355 B	sag. Moulding & patching purpose.	mould.	1	
7	Asacast 8275 A	Low viscosity, transparent. Casting &	Potting or encapsulation, protect LED light	2	30 mins.
	Asacast 8275 B	laminating.	from moisture.	1	
8	Asacoat 313 A	Solvent based, low viscosity, low cost.	General coating for wall, floor, coating and etc.	5	30 mins.
	Asacoat 313 B	Coating & primer purpose.		1	
9	Asasin 4851A	Low viscosity, transparent and flexible.	Sticker industry, laminating on printed stickers.	2	30 mins.
	Asahard 4851 B	Laminating & flooring purpose.	LED light lamination.	1	
10	Asalam NHP A	Light weight putty. Moulding & patching	Paper pulp mould backing system.	1	30 mins.
	Asalam NHP B	purpose.		1	
11	Asaputty 747 A	Paste form, fast curing, good hardness putty.	Mould repairing. Jigs & fixtures.	1	20 mins.
	Asaputty 747 B	Kneadable dough,		1	
12	Asaglu 3C A	High paste form adhesive. Non sag.	Adhesive for metal, wood, PU, polyester,	1	30 mins.
	Asaglu 3C B		and etc.	1	
13	Asawoodputty ASC A	Light weight wood putty, easy for sanding and	Mock up, prototyping wood putty.	1	45 mins.
	Asawoodputty ASC B	sculpturing.		1	
14	Asacast 388 A	Low viscosity, milky colour, machinable	Material for Jigs & fixtures, moulding,	5	30 mins.
	Asacast 388 B	and sandable. Casting purpose.	prototyping.	1	
15	Asacoat 3072 A	Epoxy coating, cured on wet or damp surface.	Prevent water leaking of pond & fountain.	10	30 mins.
	Asacoat 3072 B		Water proofing job.	3	
16	Asacast 433 A	Low viscosity, good electrical insulation,	Potting/encapsulation system for magnetic	2	30 mins.
	Asacast 433 B	suitable for volume casting.	door lock, transformer & etc.	1	
17	Asaflexicoat 8182 A	Flexible, medium viscosity. Coating on	Tennis court coating or road coating.	2	20 mins.
	Asaflexicoat 8182 B	bitumen road or soft floor.		3	
18	Asasin 142 A	Very low viscosity, slow curing, transparent.	Souvenirs industry, artificial crystal, toys,	100	120 mins.
	Asahard 142 B	Laminating & flooring purpose.	statues and etc. Volume casting.	42	
19	Asamortar CV 1091 A	Mortar mix with sand to increase hardness &	Backing system for PU injection mould &	100	20 mins.
	Asamortar CV 1091 B	lower down costing.	Base coat of self leveling flooring system.	35	
20	Asasin 8505 A	Low viscosity, transparent. Hard with good	Backing system of laminating epoxy mould,	2	30 mins.
	Asahard 8505 B	clarity. Laminating & flooring purpose.	also for tank lining. Flooring.	1	